



RESERVOIR ROTERRA DRIVE

- ♻️ **Can be installed in road surfaces (load class D400)**
- ♻️ **Easy cleaning and maintenance of the reservoirs interior**
- ♻️ **Long product life and recyclability**
- ♻️ **Quick installation and easy on-site handling**
- ♻️ **Suitable for various applications**
- ♻️ **Adaptable to ground elevations**
- ♻️ **Option of additional equipment according to the project (suction hoses, filters, etc.)**
- ♻️ **Slovenian product**

Product description

RoDrive tanks are suitable for a variety of uses and applications. They can be used as fire water tanks, water retention tanks, water storage tanks and more.

They are characterised by excellent statics, allowing the tank to be installed in road surfaces up to load class D 400 or axle loads up to 40 t/m².

Technical specifications

| VOLUME [L] | Material | Load class | Dimensions [L x D x H] [mm] | Inlet/outlet pipe | Net weight |
|------------|-------------------|------------|-----------------------------|-------------------|------------|
| 40.000 L | polyethylene [PE] | D 400 | 8.510 x 2.450 x 3.720 mm | By project | 1000 kg |

Reservoir installation

The RoDrive tank must be installed in accordance with the manufacturer's instructions, which are available on the QR code. For further information or to have a technical team present when the product is installed, please contact projekt@roto.si or visit www.rotoECO.eu.

